

Evaluation of Relational Operations

[R&G] Chapter 14, Part A (Joins)

Relational Operations

- ❖ We will consider how to implement:
 - **Selection** (σ) Selects a subset of rows from relation.
 - **Projection** (π) Deletes unwanted columns from relation.
 - **Join** (\bowtie) Allows us to combine two relations.
 - **Set-difference** ($-$) Tuples in reln. 1, but not in reln. 2.
 - **Union** (\cup) Tuples in reln. 1 and in reln. 2.
 - **Aggregation** (SUM, MIN, etc.) and GROUP BY
- ❖ Since each op returns a relation, ops can be *composed!*
After we cover the operations, we will discuss how to *optimize* queries formed by composing them.

Schema for Examples

Sailors (*sid*: integer, *sname*: string, *rating*: integer, *age*: real)
Reserves (*sid*: integer, *bid*: integer, *day*: dates, *rname*: string)

- ❖ Similar to old schema; *rname* added for variations.
- ❖ Reserves:
 - Each tuple is 40 bytes long, 100 tuples per page, 1000 pages.
- ❖ Sailors:
 - Each tuple is 50 bytes long, 80 tuples per page, 500 pages.

Equality Joins With One Join Column

```
SELECT *
FROM Reserves R1, Sailors S1
WHERE R1.sid=S1.sid
```

- ❖ In algebra: $R \bowtie S$. Common! Must be carefully optimized. $R \times S$ is large; so, $R \times S$ followed by a selection is inefficient.
- ❖ Assume: M pages in R, p_R tuples per page, N pages in S, p_S tuples per page.
 - In our examples, R is Reserves and S is Sailors.
- ❖ We will consider more complex join conditions later.
- ❖ **Cost metric:** # of I/Os. We will ignore output costs.

Simple Nested Loops Join

```
foreach tuple r in R do
  foreach tuple s in S do
    if  $r_i == s_j$  then add  $\langle r, s \rangle$  to result
```

- ❖ For each tuple in the *outer* relation R, we scan the entire *inner* relation S.
 - **Cost:** $M + p_R * M * N = 1000 + 100 * 1000 * 500$ I/Os.
- ❖ Page-oriented Nested Loops join: For each *page* of R, get each *page* of S, and write out matching pairs of tuples $\langle r, s \rangle$, where r is in R-page and S is in S-page.
 - **Cost:** $M + M * N = 1000 + 1000 * 500$
- ❖ If the smaller relation (S) is outer, cost = $500 + 500 * 1000$

Index Nested Loops Join

```
foreach tuple r in R do
  foreach tuple s in S where  $r_i == s_j$  do
    add  $\langle r, s \rangle$  to result
```

- ❖ If there is an index on the join column of one relation (say S), can make it the inner and exploit the index.
 - **Cost:** $M + (M * p_R) * \text{cost of finding matching S tuples}$
- ❖ For each R tuple, cost of probing S index is about 1.2 for hash index, 2-4 for B+ tree. Cost of then finding S tuples (assuming Alt. (2) or (3) for data entries) depends on clustering.
 - **Clustered index:** 1 I/O (typical), **unclustered:** upto 1 I/O per matching S tuple.

Examples of Index Nested Loops


- ❖ Hash-index (Alt. 2) on *sid* of Sailors (as inner):
 - Scan Reserves: 1000 page I/Os, 100*1000 tuples.
 - For each Reserves tuple: 1.2 I/Os to get data entry in index, plus 1 I/O to get (the exactly one) matching Sailors tuple. Total: 220,000 I/Os.
- ❖ Hash-index (Alt. 2) on *sid* of Reserves (as inner):
 - Scan Sailors: 500 page I/Os, 80*500 tuples.
 - For each Sailors tuple: 1.2 I/Os to find index page with data entries, plus cost of retrieving matching Reserves tuples. Assuming uniform distribution, 2.5 reservations per sailor (100,000 / 40,000). Cost of retrieving them is 1 or 2.5 I/Os depending on whether the index is clustered.

CS432 Fall 2007

7

Block Nested Loops Join

- ❖ Use one page as an input buffer for scanning the inner S, one page as the output buffer, and use all remaining pages to hold "block" of outer R.
 - For each matching tuple *r* in R-block, *s* in S-page, add $\langle r, s \rangle$ to result. Then read next R-block, scan S, etc.



CS432 Fall 2007

8

Examples of Block Nested Loops

- ❖ **Cost:** Scan of outer + #outer blocks * scan of inner
 - #outer blocks = $\lceil \# \text{ of pages of outer} / \text{blocksize} \rceil$
- ❖ With Reserves (R) as outer, and 100 pages of R:
 - Cost of scanning R is 1000 I/Os; a total of 10 blocks.
 - Per block of R, we scan Sailors (S); 10*500 I/Os.
 - If space for just 90 pages of R, we would scan S 12 times.
- ❖ With 100-page block of Sailors as outer:
 - Cost of scanning S is 500 I/Os; a total of 5 blocks.
 - Per block of S, we scan Reserves; 5*1000 I/Os.
- ❖ With sequential reads considered, analysis changes: may be best to divide buffers evenly between R and S.

CS432 Fall 2007

9

Sort-Merge Join ($R \bowtie_{i=j} S$)

- ❖ Sort R and S on the join column, then scan them to do a “merge” (on join col.), and output result tuples.
 - Advance scan of R until current R-tuple \geq current S tuple, then advance scan of S until current S-tuple \geq current R tuple; do this until current R tuple = current S tuple.
 - At this point, all R tuples with same value in R_i (current R group) and all S tuples with same value in S_j (current S group) *match*; output $\langle r, s \rangle$ for all pairs of such tuples.
 - Then resume scanning R and S.
- ❖ R is scanned once; each S group is scanned once per matching R tuple. (Multiple scans of an S group are likely to find needed pages in buffer.)

CS432 Fall 2007

10

Example of Sort-Merge Join

sid	sname	rating	age	sid	bid	day	rname
22	dustin	7	45.0	28	103	12/4/96	guppy
28	yuppy	9	35.0	28	103	11/3/96	yuppy
31	lubber	8	55.5	31	101	10/10/96	dustin
44	guppy	5	35.0	31	102	10/12/96	lubber
58	rusty	10	35.0	31	101	10/11/96	lubber
				58	103	11/12/96	dustin

- ❖ **Cost:** $M \log M + N \log N + (M+N)$
 - The cost of scanning, $M+N$, could be $M*N$ (very unlikely!)
- ❖ With 35, 100 or 300 buffer pages, both Reserves and Sailors can be sorted in 2 passes; total join cost: 7500.
(BNL cost: 2500 to 15000 I/Os)

CS432 Fall 2007

11

Refinement of Sort-Merge Join

- ❖ We can combine the merging phases in the *sorting* of R and S with the merging required for the join.
 - With $B > \sqrt{L}$, where L is the size of the larger relation, using the sorting refinement that produces runs of length $2B$ in Pass 0, #runs of each relation is $< B/2$.
 - Allocate 1 page per run of each relation, and “merge” while checking the join condition.
 - **Cost:** read+write each relation in Pass 0 + read each relation in (only) merging pass (+ writing of result tuples).
 - In example, cost goes down from 7500 to 4500 I/Os.
- ❖ In practice, cost of sort-merge join, like the cost of external sorting, is *linear*.

CS432 Fall 2007

12

General Join Conditions

- ❖ Equalities over several attributes (e.g., $R.sid=S.sid$ AND $R.rname=S.rname$):
 - For Index NL, build index on $\langle sid, rname \rangle$ (if S is inner); or use existing indexes on sid or $rname$.
 - For Sort-Merge and Hash Join, sort/partition on combination of the two join columns.
- ❖ Inequality conditions (e.g., $R.rname < S.rname$):
 - For Index NL, need (clustered!) B+ tree index.
 - Range probes on inner; # matches likely to be much higher than for equality joins.
 - Hash Join, Sort Merge Join not applicable.
 - Block NL quite likely to be the best join method here.
